

### HIGH-TEMPERATURE, 40V N-CHANNEL POWER MOSFET FAMILY

#### FEATURES

- ▲ Minimum  $V_{DS} = 55V$ .
- ▲ Allowed  $V_{GS}$  range  $-5.5V$  to  $+5.5V$ .
- ▲ Operational beyond the  $-60^{\circ}C$  to  $+230^{\circ}C$  temperature range.
- ▲ Low  $R_{DS(on)}$ 
  - XTR2N0425: 560 m $\Omega$  @ 230 $^{\circ}C$
  - XTR2N0450: 255 m $\Omega$  @ 230 $^{\circ}C$
- ▲ Maximum  $I_D$ :
  - XTR2N0425: 4.7A @ 230 $^{\circ}C$
  - XTR2N0450: 10.3A @ 230 $^{\circ}C$
- ▲ On-time ( $t_{d(on)}+t_r$ ):
  - XTR2N0425: 25nsec @ 230 $^{\circ}C$
  - XTR2N0450: 30nsec @ 230 $^{\circ}C$
- ▲ Off-time ( $t_{d(off)}+t_f$ ):
  - XTR2N0425: 56nsec @ 230 $^{\circ}C$
  - XTR2N0450: 68nsec @ 230 $^{\circ}C$
- ▲ Ruggedized 3-lead TO257, 8-lead side brazed DIP and 8-lead SOIC with ePAD.
- ▲ Also available as bare die.

#### DESCRIPTION


XTR2N0400 is a family of N-channel power MOSFETs designed to reliably operate over a wide range of temperatures. Full functionality is guaranteed from  $-60^{\circ}C$  to  $+230^{\circ}C$ , though operation well below and above this temperature range is achieved. Fabricated on a Silicon-on-Insulator (SOI) process, XTR2N0400 family parts offer reduced leakage currents while providing high drain currents a low  $R_{DS(on)}$ . These features allow XTR2N0400 parts to be ideally suited for switching applications. XTR2N0400 family parts have been designed to reduce system cost and ease adoption by reducing the learning curve and providing smart and easy to use features. Parts from the XTR2N0400 family are available in ruggedized 3-lead TO257, 8-lead side brazed DIP. Parts are also available as tested bare die.

#### APPLICATIONS


- ▲ Reliability-critical, Automotive, Aeronautics & Aerospace, Down-hole.
- ▲ DC/DC converters, power switching, motor control, power inverters, power linear regulators, power supply.

#### PRODUCT HIGHLIGHT

Power Series Regulator



Step-down DC-DC Converter



#### ORDERING INFORMATION



| Product Reference | Temperature Range                 | Package                | Pin Count | Marking   |
|-------------------|-----------------------------------|------------------------|-----------|-----------|
| XTR2N0425-D       | $-60^{\circ}C$ to $+230^{\circ}C$ | Ceramic side Braze DIP | 8         | XTR2N0425 |
| XTR2N0425-T       | $-60^{\circ}C$ to $+230^{\circ}C$ | TO-257                 | 3         | XTR2N0425 |
| XTR2N0425-TD      | $-60^{\circ}C$ to $+230^{\circ}C$ | Tested bare die        |           |           |
| XTR2N0450-TD      | $-60^{\circ}C$ to $+230^{\circ}C$ | Tested bare die        |           |           |


Other packages and packaging configurations possible upon request. For some packages or packaging configurations, MOQ may apply.

## ABSOLUTE MAXIMUM RATINGS

|                                      |                     |
|--------------------------------------|---------------------|
| Drain-source voltage                 | -2V to +55V         |
| Gate-source voltage                  | ±6.0V               |
| Storage temperature range            | -70°C to +230°C     |
| Operating junction temperature range | -70°C to +300°C     |
| ESD classification                   | 2kV HBM MIL-STD-750 |

**Caution:** Stresses beyond those listed in “ABSOLUTE MAXIMUM RATINGS” may cause permanent damage to the device. These are stress ratings only and functionality of the device at these or any other condition beyond those indicated in the operational sections of the specifications is not implied. Exposure to “ABSOLUTE MAXIMUM RATINGS” conditions for extended periods may permanently affect device reliability.

## PRODUCT VARIANTS



## THERMAL CHARACTERISTICS

| Parameter                                | Condition  | Min | Typ | Max | Units |
|--|------------|-----|-----|-----|-------|
| <b>XTR2N0425-T (TO257)</b>               |            |     |     |     |       |
| Thermal Resistance: J-C<br>$R_{Th, J-C}$ |            |     | 5   |     | °C/W  |
| Thermal Resistance: J-A<br>$R_{Th, J-A}$ | Still air. |     | 50  |     | °C/W  |
| <b>XTR2N0425-D (DIP8)</b>                |            |     |     |     |       |
| Thermal Resistance: J-C<br>$R_{Th, J-C}$ |            |     | 20  |     | °C/W  |
| Thermal Resistance: J-A<br>$R_{Th, J-A}$ | Still air. |     | 100 |     | °C/W  |

**RECOMMENDED OPERATING CONDITIONS**

| Parameter                                  | Min  | Typ | Max  | Units |
|--|------|-----|------|-------|
| Drain-source voltage<br>$V_{DS}$           | -1.5 |     | 40   | V     |
| Gate-source voltage<br>$V_{GS}$            | -5.5 |     | +5.5 | V     |
| Junction Temperature <sup>1</sup><br>$T_j$ | -60  |     | 230  | °C    |

<sup>1</sup> Operation beyond the specified temperature range is achieved. The -60°C to +230°C range for the case temperature is considered for the case where  $I_D \leq I_{D(DC)}$  for a given case temperature.

**XTR2N0425 SPECIFICATIONS**

Unless otherwise stated, specification applies for -60°C <  $T_j$  < 230°C.

| Parameter   | Condition   | Min                  | Typ                  | Max               | Units |
|---|---|----------------------|----------------------|-------------------|-------|
| <b>DC Characteristics</b>   |   |                      |                      |                   |       |
| Drain-source breakdown voltage<br>$BV_{DSS}$                                  | $V_{GS}=0V, I_{DS}=100\mu A$  | 55                   |                      |                   | V     |
| Static drain-source on-state resistance<br>$R_{DS(on)}$                       | $V_{GS}=+5V, I_{DS}=100mA$<br>$T_C=-60^\circ C$<br>$T_C=85^\circ C$<br>$T_C=230^\circ C$                                |                      | 230<br>360<br>560    | 280<br>430<br>670 | mΩ    |
| Continuous drain current<br>$I_{D(DC)}$                                       | $V_{GS}=+5V$ for TO-257<br>$T_J=-60^\circ C$<br>$T_J=85^\circ C$<br>$T_J=230^\circ C$                                   | 1.75<br>1.25<br>0.95 | 2.2<br>1.6<br>1.2    |                   | A     |
| Gate threshold voltage<br>$V_{GS(th)}$  | $V_{DS}=V_{GS}, I_{DS}=1mA$<br>$T_C=-60^\circ C$<br>$T_C=85^\circ C$<br>$T_C=230^\circ C$                               |                      | 1.76<br>1.38<br>0.89 |                   | V     |
| Temperature drift of gate threshold voltage<br>$\Delta V_{GS(th)}/\Delta T_j$ | $V_{DS}=V_{GS}, I_{DS}=1mA$   |                      | -3.0                 |                   | mV/°C |
| Off-state drain current<br>$I_{DSS}$  | $V_{DS}=40V, V_{GS}=0V$<br>$T_C=85^\circ C$<br>$T_C=230^\circ C$  |                      | 0.01<br>13           | 0.5<br>60         | μA    |
| Gate Leakage current<br>$I_{GSS}$   | $V_{GS}=\pm 5V, V_{DS}=0V$<br>$T_C=85^\circ C$<br>$T_C=230^\circ C$   |                      | ±0.6<br>±130         | ±5<br>±1000       | nA    |
| <b>AC Characteristics</b>   |   |                      |                      |                   |       |
| Input capacitance<br>$C_{iss}$  | $V_{DS}=32V, V_{GS}=0V, f=1MHz$   |                      | 390                  |                   | pF    |
| Output capacitance<br>$C_{oss}$   |   |                      | 80                   |                   | pF    |
| Transfer capacitance<br>$C_{rss}$   |   |                      | 65                   |                   | pF    |
| <b>Switching Characteristics</b>  |   |                      |                      |                   |       |
| Pulsed drain current<br>$I_{DM}$  | $V_{DS}=20V, V_{GS\ sweep}=0$ to +5V, $d=0.2\%, \tau=1ms$<br>$T_C=-60^\circ C$<br>$T_C=85^\circ C$<br>$T_C=230^\circ C$ | 7.0<br>5.0<br>3.8    | 8.8<br>6.2<br>4.7    |                   | A     |
| Total gate charge<br>$Q_g$  | $V_{DS}=20V, V_{GS\ sweep}=0$ to +5V  |                      | 5.4                  |                   | nC    |
| Turn-on delay time<br>$t_{d(on)}$   | $V_{DS}=20V, V_{GS\ sweep}=0$ to +5V, $R_D=47\Omega, d=0.2\%, \tau=1ms$   |                      | 11                   |                   | ns    |
| Rise time<br>$t_r$  | $V_{DS}=20V, V_{GS\ sweep}=0$ to +5V, $R_D=47\Omega, d=0.2\%, \tau=1ms$   |                      | 14                   |                   |       |
| Turn-off delay time<br>$t_{d(off)}$   | $V_{DS}=20V, V_{GS\ sweep}=0$ to +5V, $R_D=47\Omega, d=0.2\%, \tau=1ms$   |                      | 29                   |                   |       |
| Fall time<br>$t_f$  | $V_{DS}=20V, V_{GS\ sweep}=0$ to +5V, $R_D=47\Omega, d=0.2\%, \tau=1ms$   |                      | 27                   |                   |       |
| <b>Drain-Source Diode Characteristics</b>                                     |   |                      |                      |                   |       |
| Forward diode voltage<br>$V_{SD\_1A}$   | $V_{GS}=0V, I_{DS}=-1A$<br>$T_C=-60^\circ C$<br>$T_C=85^\circ C$<br>$T_C=230^\circ C$                                   |                      | 1.10<br>0.97<br>0.89 |                   | V     |

**XTR2N0450 SPECIFICATIONS**

 Unless otherwise stated, specification applies for  $-60^{\circ}\text{C} < T_j < 230^{\circ}\text{C}$ .

| Parameter   | Condition   | Min                 | Typ                    | Max                   | Units                        |
|---|---|---------------------|------------------------|-----------------------|------------------------------|
| <b>DC Characteristics</b>   |   |                     |                        |                       |                              |
| Drain-source breakdown voltage<br>$BV_{DSS}$                                  | $V_{GS}=0\text{V}, I_{DS}=100\mu\text{A}$   | 55                  |                        |                       | V                            |
| Static drain-source on-state resistance<br>$R_{DS(on)}$                       | $V_{GS}=+5\text{V}, I_{DS}=100\text{mA}$<br>$T_C=-60^{\circ}\text{C}$<br>$T_C=85^{\circ}\text{C}$<br>$T_C=230^{\circ}\text{C}$  |                     | 105<br>165<br>255      | 130<br>200<br>310     | $\text{m}\Omega$             |
| Continuous drain current<br>$I_{D(DC)}$                                       | $V_{GS}=+5\text{V}$ for TO-257<br>$T_J=-60^{\circ}\text{C}$<br>$T_J=85^{\circ}\text{C}$<br>$T_J=230^{\circ}\text{C}$  | 3.8<br>2.7<br>2.1   | 4.8<br>3.4<br>2.6      |                       | A                            |
| Gate threshold voltage<br>$V_{GS(th)}$  | $V_{DS}=V_{GS}, I_{DS}=1\text{mA}$<br>$T_C=-60^{\circ}\text{C}$<br>$T_C=85^{\circ}\text{C}$<br>$T_C=230^{\circ}\text{C}$  |                     | 1.72<br>1.32<br>0.79   |                       | V                            |
| Temperature drift of gate threshold voltage<br>$\Delta V_{GS(th)}/\Delta T_j$ | $V_{DS}=V_{GS}, I_{DS}=1\text{mA}$  |                     | -3.2                   |                       | $\text{mV}/^{\circ}\text{C}$ |
| Off-state drain current<br>$I_{DSS}$  | $V_{DS}=40\text{V}, V_{GS}=0\text{V}$<br>$T_C=85^{\circ}\text{C}$<br>$T_C=230^{\circ}\text{C}$  |                     | 0.02<br>30             | 1<br>150              | $\mu\text{A}$                |
| Gate Leakage current<br>$I_{GSS}$   | $V_{GS}=\pm 5\text{V}, V_{DS}=0\text{V}$<br>$T_C=85^{\circ}\text{C}$<br>$T_C=230^{\circ}\text{C}$   |                     | $\pm 0.8$<br>$\pm 160$ | $\pm 5$<br>$\pm 1000$ | nA                           |
| <b>AC Characteristics</b>   |   |                     |                        |                       |                              |
| Input capacitance<br>$C_{iss}$  | $V_{DS}=32\text{V}, V_{GS}=0\text{V}, f=1\text{MHz}$  |                     | 900                    |                       | pF                           |
| Output capacitance<br>$C_{oss}$   |   |                     | 180                    |                       | pF                           |
| Transfer capacitance<br>$C_{rss}$   |   |                     | 150                    |                       | pF                           |
| <b>Switching Characteristics</b>  |   |                     |                        |                       |                              |
| Pulsed drain current<br>$I_{DM}$  | $V_{DS}=20\text{V}, V_{GS \text{ sweep}}=0$ to +5V, $d=0.2\%$ , $\tau=1\text{ms}$<br>$T_C=-60^{\circ}\text{C}$<br>$T_C=85^{\circ}\text{C}$<br>$T_C=230^{\circ}\text{C}$ | 15.5<br>10.9<br>8.3 | 19.4<br>13.6<br>10.3   |                       | A                            |
| Total gate charge<br>$Q_g$  | $V_{DS}=20\text{V}, V_{GS \text{ sweep}}=0$ to +5V  |                     | 12.2                   |                       | nC                           |
| Turn-on delay time<br>$t_{d(on)}$   | $V_{DS}=20\text{V}, V_{GS \text{ sweep}}=0$ to +5V, $R_D=47\Omega, d=0.2\%$ , $\tau=1\text{ms}$   |                     | 13                     |                       | ns                           |
| Rise time<br>$t_r$  | $V_{DS}=20\text{V}, V_{GS \text{ sweep}}=0$ to +5V, $R_D=47\Omega, d=0.2\%$ , $\tau=1\text{ms}$   |                     | 17                     |                       |                              |
| Turn-off delay time<br>$t_{d(off)}$   | $V_{DS}=20\text{V}, V_{GS \text{ sweep}}=0$ to +5V, $R_D=47\Omega, d=0.2\%$ , $\tau=1\text{ms}$   |                     | 35                     |                       |                              |
| Fall time<br>$t_f$  | $V_{DS}=20\text{V}, V_{GS \text{ sweep}}=0$ to +5V, $R_D=47\Omega, d=0.2\%$ , $\tau=1\text{ms}$   |                     | 33                     |                       |                              |
| <b>Drain-Source Diode Characteristics</b>                                     |   |                     |                        |                       |                              |
| Forward diode voltage<br>$V_{SD-1A}$  | $V_{GS}=0\text{V}, I_{DS}=-1\text{A}$<br>$T_C=-60^{\circ}\text{C}$<br>$T_C=85^{\circ}\text{C}$<br>$T_C=230^{\circ}\text{C}$   |                     | 1.00<br>0.88<br>0.66   |                       | V                            |

## XTR2N0425 TYPICAL PERFORMANCE




Figure 1. Drain Current ( $I_{DS}$ ) vs Gate-Source Voltage for several case temperatures.  $V_{DS}=50mV$ .




Figure 2. Gate-Source Threshold Voltage ( $V_{GS(th)}$ ) vs Gate-Source Voltage for several case temperatures.  $V_{GS}=V_{DS}$ .




Figure 3. Drain-Source ON Resistance ( $R_{DS(on)}$ ) vs Gate-Source Voltage for several case temperatures.  $V_{DS}=50mV$ .




Figure 4. Drain-Source ON Resistance ( $R_{DS(on)}$ ) vs Case Temperature.  $V_{DS}=50mV$ .




Figure 5. Drain Current ( $I_{DS}$ ) vs Gate-Source Voltage for several case temperatures.  $V_{GS}=V_{DS}$




Figure 6. Body Diode Forward Current ( $I_{FD}$ ) vs Forward Voltage for several case temperature.  $V_{GS}=0V$ .

## XTR2N0425 TYPICAL PERFORMANCE (CONTINUED)




Figure 7. Off-State Drain Current ( $I_{DSS}$ ) vs Case Temperature.  $V_{DS}=40V$ ,  $V_{GS}=0V$ .




Figure 8. Gate Leakage Current ( $I_{GSS}$ ) vs Case Temperature.  $V_{GS}=\pm 5V$ ,  $V_{DS}=0V$ .




Figure 9. Pulsed Drain Current ( $I_{DM}$ ) vs Drain-Source Voltage for several case temperatures.  $V_{GS}=3V, 4V$  and  $5V$ .




Figure 10. Total Gate Charge ( $Q_g$ ) vs Gate-Source Voltage for several case temperatures.  $I_{DS}=900mA$ .




Figure 11. Timing Characteristics vs Case Temperature.  $V_{DS}=20V$ ,  $V_{GS}$  sweep = 0 to 5V.




Figure 12. Capacitance vs Drain-Source Voltage at  $T_c=25^\circ C$ .

## XTR2N0450 TYPICAL PERFORMANCE




Figure 13. Drain Current ( $I_{DS}$ ) vs Gate-Source Voltage for several case temperatures.  $V_{DS}=50mV$ .




Figure 14. Gate-Source Threshold Voltage ( $V_{GS(th)}$ ) vs Case Temperature.  $V_{GS}=V_{DS}$ .




Figure 15. Drain-Source ON Resistance ( $R_{DS(on)}$ ) vs Gate-Source Voltage for several case temperatures.  $V_{DS}=50mV$ .




Figure 16. Drain-Source ON Resistance ( $R_{DS(on)}$ ) vs Case Temperature.  $V_{DS}=50mV$ .




Figure 17. Drain Current ( $I_{DS}$ ) vs Gate-Source Voltage for several case temperatures.  $V_{GS}=V_{DS}$




Figure 18. Body Diode Forward Current ( $I_{FD}$ ) vs Forward Voltage for several case temperature.  $V_{GS}=0V$ .

## XTR2N0450 TYPICAL PERFORMANCE (CONTINUED)




Figure 19. Off-State Drain Current ( $I_{DSS}$ ) vs Case Temperature.  $V_{DS}=40V$ ,  $V_{GS}=0V$ .




Figure 20. Gate Leakage Current ( $I_{GSS}$ ) vs Case Temperature.  $V_{GS}=\pm 5V$ ,  $V_{DS}=0V$ .




Figure 21. Pulsed Drain Current ( $I_{DM}$ ) vs Drain-Source Voltage for several case temperatures.  $V_{GS}=3V, 4V$  and  $5V$ .




Figure 22. Total Gate Charge ( $Q_g$ ) vs Gate-Source Voltage for several case temperatures.  $I_D=900mA$ .




Figure 23. Timing Characteristics vs Case Temperature.  $V_{DS}=20V$ ,  $V_{GS\ sweep}= 0$  to  $5V$ .




Figure 24. Capacitance vs Drain-Source Voltage at  $T_c=25^\circ C$ .



**PARAMETER DEFINITION**




Figure 25. Timing diagram definition.



**IMPORTANT NOTICE & DISCLAIMER**

Information in this document supersedes and replaces all information previously supplied. Information in this document is provided solely in connection with X-REL Semiconductor products.

The information contained herein is believed to be reliable. X-REL Semiconductor makes no warranties regarding the information contained herein. X-REL Semiconductor assumes no responsibility or liability whatsoever for any of the information contained herein. X-REL Semiconductor assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. X-REL Semiconductor reserves the right to make changes, corrections, modifications or improvements, to this document and the information herein without notice. Customers should obtain and verify the latest relevant information before placing orders for X-REL Semiconductor products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

Unless expressly approved in writing by an authorized representative of X-REL Semiconductor, X-REL Semiconductor products are not designed, authorized or warranted for use in military, aircraft, space, life saving, or life sustaining applications, nor in products or systems where failure or malfunction may result in personal injury, death, or property or environmental damage.

General Sales Terms & Conditions apply.

**CONTACT US**

For more information on X-REL Semiconductor's products, technical support or ordering:

- ✓ Web: [www.x-relsemi.com/products](http://www.x-relsemi.com/products)
- ✓ Tel: +33 456 580 580
- ✓ Fax: +33 456 580 599
- ✓ Sales: [sales@x-relsemi.com](mailto:sales@x-relsemi.com)  
[www.x-relsemi.com/EN/Sales-Representatives](http://www.x-relsemi.com/EN/Sales-Representatives)
- ✓ Information: [info@x-relsemi.com](mailto:info@x-relsemi.com)
- ✓ Support: [support@x-relsemi.com](mailto:support@x-relsemi.com)

**X-REL Semiconductor**

90, Avenue Léon Blum  
38100 Grenoble  
France