

HIGH-TEMPERATURE, 80V N-CHANNEL SMALL SIGNAL MOSFET

FEATURES

- ▲ Minimum $BV_{DSS} = 90V$.
- ▲ Allowed V_{GS} range $-5.5V$ to $+5.5V$.
- ▲ Operational beyond the $-60^{\circ}C$ to $+230^{\circ}C$ temperature range.
- ▲ Low $R_{DS(on)}$
 - XTR2N0807: $9.5\Omega @ 230^{\circ}C$
- ▲ Maximum I_D :
 - XTR2N0807: $600mA @ 230^{\circ}C$
- ▲ On-time ($t_{d(on)}+t_r$):
 - XTR2N0807: $12nsec @ 230^{\circ}C$
- ▲ Off-time ($t_{d(off)}+t_f$):
 - XTR2N0807: $33nsec @ 230^{\circ}C$
- ▲ Available in ruggedized SMT and thru-hole packages.
- ▲ Parts are also available as bare dies.


DESCRIPTION

XTR2N0807 is an N-channel small signal MOSFETs designed to reliably operate over a wide range of temperatures. Full functionality is guaranteed from $-60^{\circ}C$ to $+230^{\circ}C$, though operation well below and above this temperature range is achieved. Fabricated on a Silicon-on-Insulator (SOI) process, XTR2N0807 family parts offer reduced leakage currents while providing high drain currents and low $R_{DS(on)}$. These features allow XTR2N0807 parts to be ideally suited for switching applications. XTR2N0807 family parts have been designed to reduce system cost and ease adoption by reducing the learning curve and providing smart and easy to use features. XTR2N0807 parts are available ruggedized SMT and thru-hole packages. Parts are also available as bare dies.

APPLICATIONS

- ▲ Reliability-critical, Automotive, Aeronautics & Aerospace, Down-hole.
- ▲ Linear regulators, switching applications, sensor driving, level shifting.

PRODUCT HIGHLIGHT



ORDERING INFORMATION



| Product Reference | Temperature Range | Package | Pin Count | Marking |
|-------------------|-----------------------------------|-------------------------------|-----------|-----------|
| XTR2N0807-FE | $-60^{\circ}C$ to $+230^{\circ}C$ | Gull-wing flat pack with ePad | 8 | XTR2N0807 |
| XTR2N0807-T | $-60^{\circ}C$ to $+230^{\circ}C$ | TO-18 metal can | 3 | XTR2N0807 |
| XTR2N0807-TD | $-60^{\circ}C$ to $+230^{\circ}C$ | Tested bare die | | |

Other packages and packaging configurations possible upon request. For some packages or packaging configurations, MOQ may apply. Contact X-REL for plastic packaged parts.

ABSOLUTE MAXIMUM RATINGS


| | |
|--------------------------------------|---------------------|
| Drain-source voltage | -2V to +90V |
| Gate-source voltage | ±6.0V |
| Storage temperature range | -70°C to +230°C |
| Operating junction temperature range | -70°C to +300°C |
| ESD classification | 1kV HBM MIL-STD-750 |

Caution: Stresses beyond those listed in “ABSOLUTE MAXIMUM RATINGS” may cause permanent damage to the device. These are stress ratings only and functionality of the device at these or any other condition beyond those indicated in the operational sections of the specifications is not implied. Exposure to “ABSOLUTE MAXIMUM RATINGS” conditions for extended periods may permanently affect device reliability.

PRODUCT VARIANTS

CDFP8 with ePad XTR2N0807-FE


Top view



ePAD (bottom of package) connected to SOURCE

TO-18 XTR2N0807-T

Bottom view



Package case connected to SOURCE

THERMAL CHARACTERISTICS

| Parameter | Condition | Min | Typ | Max | Units |
|--|----------------------------|-----|-----|-----|-------|
| XTR2N0807-FE (DFP8) | | | | | |
| Thermal Resistance: J-C R_{Th_J-C} | Resistance to exposed pad. | | 15 | | °C/W |
| Thermal Resistance: J-A R_{Th_J-A} | | | 85 | | °C/W |
| XTR2N0807-T (TO-18) | | | | | |
| Thermal Resistance: J-C R_{Th_J-C} | | | 55 | | °C/W |
| Thermal Resistance: J-A R_{Th_J-A} | | | 300 | | °C/W |

RECOMMENDED OPERATING CONDITIONS

| Parameter | Min | Typ | Max | Units |
|--|------|-----|------|-------|
| Drain-source voltage V_{DS} | -1.5 | | 80 | V |
| Gate-source voltage V_{GS} | -5.5 | | +5.5 | V |
| Junction Temperature ¹ T_j | -60 | | 230 | °C |

¹ Operation beyond the specified temperature range is achieved. The -60°C to +230°C range for the case temperature is considered for the case where $I_D \leq I_{D(DC)}$ for a given case temperature.

XTR2N0807 SPECIFICATIONS

Unless otherwise stated, specification applies for -60°C < T_j < 230°C.

| Parameter | Condition | Min | Typ | Max | Units |
|---|--|-------------------|------------------------|----------------------|----------|
| DC Characteristics | | | | | |
| Drain-source breakdown voltage BV_{DSS} | $V_{GS}=0V, I_{DS}=100\mu A, T_j=25^\circ C$ | 90 | | | V |
| Static drain-source on-state resistance $R_{DS(on)}$ | $V_{GS}=+5V, V_{DS}=50mV$ $T_C=-60^\circ C$ $T_C=85^\circ C$ $T_C=230^\circ C$ | | 3.5 6.1 9.5 | 4.6 8.0 12.4 | Ω |
| Continuous drain current $I_{D(DC)}$ | $V_{GS}=+5V$ for T0-18 $T_j=-60^\circ C$ $T_j=85^\circ C$ $T_j=230^\circ C$ | 190 140 105 | 270 200 150 | | mA |
| Gate threshold voltage $V_{GS(th)}$ | $V_{DS}=V_{GS}, I_{DS}=1mA$ $T_C=-60^\circ C$ $T_C=85^\circ C$ $T_C=230^\circ$ | | 1.84 1.53 1.18 | | V |
| Temperature drift of gate threshold voltage $\Delta V_{GS(th)}/\Delta T_j$ | $V_{DS}=V_{GS}, I_{DS}=1mA$ | | -2.27 | | mV/°C |
| Off-state drain current I_{DSS} | $V_{DS}=80V, V_{GS}=0V$ $T_C=85^\circ C$ $T_C=230^\circ C$ | | 0.004 2.0 | 0.03 10 | μA |
| Gate Leakage current I_{GSS} | $V_{GS}=\pm 5V, V_{DS}=0V$ $T_C=85^\circ C$ $T_C=230^\circ C$ | | ± 0.9 ± 100 | ± 5 ± 700 | nA |
| AC Characteristics | | | | | |
| Input capacitance C_{iss} | $V_{DS}=40V, V_{GS}=0V, f=1MHz$ | | 38 | | pF |
| Output capacitance C_{oss} | | | 8.3 | | pF |
| Reverse transfer capacitance C_{rss} | | | 1.5 | | pF |
| Switching Characteristics | | | | | |
| Pulsed drain current I_{DM} | $V_{DS}=40V, V_{GS \text{ sweep}}=0$ to +5V, $d=0.2\%, \tau=1ms$ $T_C=-60^\circ C$ $T_C=85^\circ C$ $T_C=230^\circ C$ | 770 560 420 | 1110 800 600 | | mA |
| Total gate charge Q_g | $V_{DS}=40V, V_{GS \text{ sweep}}=0$ to +5V | | 0.62 | | nC |
| Turn-on delay time $t_{d(on)}$ | $V_{DS}=20V, V_{GS \text{ sweep}}=0$ to +5V, $R_D=100\Omega, d=0.2\%, \tau=1ms$ | | 7.2 | | ns |
| Rise time t_r | | | 4.7 | | |
| Turn-off delay time $t_{d(off)}$ | | | 10.3 | | |
| Fall time t_f | | | 22 | | |
| Drain-Source Diode Characteristics | | | | | |
| Forward diode voltage $V_{SD_{100mA}}$ | $V_{GS}=0V, I_{DS}=-100mA$ $T_C=-60^\circ C$ $T_C=85^\circ C$ $T_C=230^\circ C$ | | 1.16 1.05 0.95 | | V |


TYPICAL PERFORMANCE


Figure 1. Drain Current (I_{DS}) vs Gate-Source Voltage for several case temperatures. $V_{DS}=50mV$.




Figure 2. Gate-Source Threshold Voltage ($V_{GS(th)}$) vs Case temperatures. $V_{GS}=V_{DS}$.




Figure 3. Drain-Source ON Resistance ($R_{DS(on)}$) vs Gate-Source Voltage for several case temperatures. $V_{DS}=50mV$.




Figure 4. Drain-Source ON Resistance ($R_{DS(on)}$) vs Case Temperature. $V_{DS}=50mV$.




Figure 5. Drain Current (I_{DS}) vs Gate-Source Voltage for several case temperatures. $V_{GS}=V_{DS}$




Figure 6. Body Diode Forward Current (I_{FD}) vs Forward Voltage for several case temperature. $V_{GS}=0V$.

TYPICAL PERFORMANCE (CONTINUED)




Figure 7. Off-State Drain Current (I_{DSS}) vs Case Temperature. $V_{DS}=80V$, $V_{GS}=0V$.




Figure 8. Gate Leakage Current (I_{GSS}) vs Case Temperature. $V_{GS}=\pm 5V$, $V_{DS}=0V$.




Figure 9. Pulsed Drain Current (I_{DM}) vs Drain-Source Voltage for several case temperatures. $V_{GS}=3V$, $4V$ and $5V$.




Figure 10. Total Gate Charge (Q_g) vs Gate-Source Voltage for several case temperatures. $I_{DS}=200mA$.




Figure 11. Timing Characteristics vs Case Temperature. $V_{DS}=20V$, $V_{GS\ sweep}= 0$ to $5V$.




Figure 12. Capacitance vs Drain-Source Voltage at $T_c=25^\circ C$.

PARAMETER DEFINITION






Figure 13. Timing diagram definition.

PACKAGE OUTLINES

Dimensions shown in mm [inches]. Tolerances ± 0.13 mm [± 0.005 in] unless otherwise stated.



Part Marking Convention

| | |
|--|--|
| Part Reference: XTRPPPPP | |
| XTR | X-REL Semiconductor, high-temperature, high-reliability product (XTRM Series). |
| PPPPP | Part number (0-9, A-Z). |
| Unique Lot Assembly Code: YYWWANN | |
| YY | Two last digits of assembly year (e.g. 11 = 2011). |
| WW | Assembly week (01 to 52). |
| A | Assembly location code. |
| NN | Assembly lot code (01 to 99). |

IMPORTANT NOTICE & DISCLAIMER

Information in this document supersedes and replaces all information previously supplied. Information in this document is provided solely in connection with X-REL Semiconductor products.

The information contained herein is believed to be reliable. X-REL Semiconductor makes no warranties regarding the information contained herein. X-REL Semiconductor assumes no responsibility or liability whatsoever for any of the information contained herein. X-REL Semiconductor assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. X-REL Semiconductor reserves the right to make changes, corrections, modifications or improvements, to this document and the information herein without notice. Customers should obtain and verify the latest relevant information before placing orders for X-REL Semiconductor products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

Unless expressly approved in writing by an authorized representative of X-REL Semiconductor, X-REL Semiconductor products are not designed, authorized or warranted for use in military, aircraft, space, life saving, or life sustaining applications, nor in products or systems where failure or malfunction may result in personal injury, death, or property or environmental damage.

General Sales Terms & Conditions apply.

CONTACT US

For more information on X-REL Semiconductor's products, technical support or ordering:

- ✓ Web: www.x-relsemi.com/products
- ✓ Tel: +33 456 580 580
- ✓ Fax: +33 456 580 599
- ✓ Sales: sales@x-relsemi.com
www.x-relsemi.com/EN/Sales-Representatives
- ✓ Information: info@x-relsemi.com
- ✓ Support: support@x-relsemi.com

X-REL Semiconductor

90, Avenue Léon Blum
38100 Grenoble
France